

## Phone info



Call Redirect: false

Cell Info Refresh Rate:

Disabled



**Physical Channel Configurations:** {{mConnectionStatus=PrimaryServing,mCellBandwidthDownlinkKhz=10000,mCellBandwidthUplinkKhz=10000,mNetworkType=LTE,mFrequencyRange=LOW,mDownlinkChannelNumber=2600,mUplinkChannelNumber=20600,mContextIds=[2,3],mPhysicalCellId=300,mBand=5,mDownlinkFrequency=889000,mUplinkFrequency=844000},{mConnectionStatus=SecondaryServing,mCellBandwidthDownlinkKhz=5000,mCellBandwidthUplinkKhz=0,mNetworkType=LTE,mFrequencyRange=MID,mDownlinkChannelNumber=975,mUplinkChannelNumber=0,mContextIds=[],mPhysicalCellId=300,mBand=2,mDownlinkFrequency=1967500,mUplinkFrequency=-1},{mConnectionStatus=SecondaryServing,mCellBandwidthDownlinkKhz=15000,mCellBandwidthUplinkKhz=0,mNetworkType=LTE,mFrequencyRange=MID,mDownlinkChannelNumber=2125,mUplinkChannelNumber=0,mContextIds=[],mPhysicalCellId=300,mBand=4,mDownlinkFrequency=2127500,mUplinkFrequency=-1}}

All Cell Measurement Info:

## Phone info



**Network Slicing Config:** Unable to get slicing config.

**eUICC info:** { Available memory in bytes:1289060 }

**Set Preferred Network Type:**

GSM/WCDMA/LTE (PRL)



Mobile Radio Power



Test real satellite non-eSOS mode (Debug Build only)

Satellite Config Viewer

VoLTE Provisioned



Video Calling Provisioned



Wifi Calling Provisioned



EAB/Presence Provisioned



Cbrs Data



Enable DSDS



Set Removable eSIM as Default



RUN PING TEST

**Ping Hostname(www.google.com) IPv4:**

**Ping Hostname(www.google.com) IPv6:**

**HTTP Client Test:**

**Data Sent:** 3264 pkts, 1439035 bytes

**Data Received:** 3824 pkts, 2942509 bytes

**Number of PPP Reset Since Boot:**

**Voice Call Status:** Idle

**Message Waiting:** false

**Call Redirect:** false

**Cell Info Refresh Rate:**

Disabled



**Physical Channel Configurations:** {{mConnectionStatus=Prim  
mService=mCellResend

## Phone info



## Select phone index

Phone 1



IMEI: 355952397632871

Phone Number: { CARRIER:, UICC:, IMS: }

Current subId: -1

SubId of default data SIM: 1

IMSI: Unknown

## Current Network:

Roaming: Not Roaming

Data Service: Disconnected

## Data Network Type:

Data Raw Registration State: NOT\_REG\_OR\_SEARCHING

## Override Network Type:

Voice Service: Out of Service

## Voice Network Type:

Voice Raw Registration State: NOT\_REG\_OR\_SEARCHING

WLAN Data Raw Registration State: NOT\_REG\_SEARCHING\_E  
M

Signal Strength: -97 dBm 43 asu

DL Bandwidth (kbps): 30000

UL Bandwidth (kbps): 15000

EN-DC Available (NSA): false

DCNR Restricted (NSA): false

NR Available (NSA): false

NR State (NSA): NONE

NR Frequency: UNKNOWN

Network Slicing Config: Unable to get slicing config.

eUICC info: { Available memory in bytes:1289060 }

## Set Preferred Network Type:

GSM/WCDMA/LTE (PRL)



Mobile Radio Power



Test real satellite non-eSOS mode (Debug Build only)

Satellite Config Viewer

VoLTE Provisioned



## Phone info



## Select phone index

Phone 0



IMEI: 355952397632863

Phone Number: +14243353756 { CARRIER:, UICC:  
+14243353756, IMS:+14243353756 }

Current subId: 1

SubId of default data SIM: 1

IMSI: 311480150084317

Current Network: Spectrum

Roaming: Not Roaming

Data Service: Connected

Data Network Type: LTE

Data Raw Registration State: HOME

Override Network Type: LTE\_CA

Voice Service: In Service

Voice Network Type: LTE

Voice Raw Registration State: HOME

WLAN Data Raw Registration State: NOT\_REG\_SEARCHING

Signal Strength: -97 dBm 43 asu

DL Bandwidth (kbps): 30000

UL Bandwidth (kbps): 15000

EN-DC Available (NSA): false

DCNR Restricted (NSA): false

NR Available (NSA): false

NR State (NSA): NONE

NR Frequency: UNKNOWN

Network Slicing Config: Unable to get slicing config.

eUICC info: { Available memory in bytes:1289060 }

## Set Preferred Network Type:

GSM/WCDMA/LTE (PRL)



Mobile Radio Power



Test real satellite non-eSOS mode (Debug Build only)

Satellite Config Viewer

VoLTE Provisioned





## Phone info



EN-DC Available (NSA): false

DCNR Restricted (NSA): false

NR Available (NSA): false

NR State (NSA): NONE

NR Frequency: UNKNOWN

Network Slicing Config: Unable to get slicing config.

eUICC info: { Available memory in bytes:1289060 }

Set Preferred Network Type:

GSM/WCDMA/LTE (PRL)



Mobile Radio Power



Test real satellite non-eSIM mode (Debug Build only)

Satellite Config Viewer

VoLTE Provisioned



Video Calling Provisioned



Wifi Calling Provisioned



EAB/Presence Provisioned



Cbrs Data



Enable eSIM



eSIM as Default



Phone Info

Number of SIM slots: 2

Available SIM slots:

Cellular Network Info:

Model:

Physical Shared eSIMs:

eSIM 1:

eSIM 2:

eSIM 3:

eSIM 4:

eSIM 5:

eSIM 6:

eSIM 7:

eSIM 8:

eSIM 9:

eSIM 10:

eSIM 11:

eSIM 12:

EST

e(www.google.com) IPv4:

e(www.google.com) IPv6:

est:

57 pkts, 1438659 bytes

Data Received: 2815 pkts, 2942017 bytes

Boot:



## Phone info



## Number of PPP Reset Since Boot:

Voice Call Status: Idle

Message Waiting: false

Call Redirect: false

## Cell Info Refresh Rate:

Disabled



**Physical Channel Configurations:** {{mConnectionStatus=PrimaryServing,mCellBandwidthDownlinkKhz=10000,mCellBandwidthUplinkKhz=10000,mNetworkType=LTE,mFrequencyRange=LOW,mDownlinkChannelNumber=2600,mUplinkChannelNumber=20600,mContextIds=[2,3],mPhysicalCellId=300,mBand=5,mDownlinkFrequency=889000,mUplinkFrequency=844000},{mConnectionStatus=SecondaryServing,mCellBandwidthDownlinkKhz=5000,mCellBandwidthUplinkKhz=0,mNetworkType=LTE,mFrequencyRange=MID,mDownlinkChannelNumber=975,mUplinkChannelNumber=0,mContextIds=[],mPhysicalCellId=300,mBand=2,mDownlinkFrequency=1967500,mUplinkFrequency=-1},{mConnectionStatus=SecondaryServing,mCellBandwidthDownlinkKhz=15000,mCellBandwidthUplinkKhz=0,mNetworkType=LTE,mFrequencyRange=MID,mDownlinkChannelNumber=2125,mUplinkChannelNumber=0,mContextIds=[],mPhysicalCellId=300,mBand=4,mDownlinkFrequency=2127500,mUplinkFrequency=-1}}

## All Cell Measurement Info:

## Last Provisioning Info

05-05 23:25:50.419

## Phone info



## Select phone index

Phone 0



IMEI: 355952397632863

Phone Number: +14243353756 { CARRIER:, UICC:  
+14243353756, IMS:+14243353756 }

Current subId: 1

SubId of default data SIM: 1

IMSI: 311480150084317

Current Network: Spectrum

Roaming: Not Roaming

Data Service: Connected

Data Network Type: LTE

Data Raw Registration State: HOME

Override Network Type: LTE\_CA

Voice Service: In Service

Voice Network Type: LTE

Voice Raw Registration State: HOME

WLAN Data Raw Registration State: NOT\_REG\_SEARCHING

Signal Strength: -97 dBm 43 asu

DL Bandwidth (kbps): 14

UL Bandwidth (kbps): 14

EN-DC Available (NSA): false

DCNR Restricted (NSA): false

NR Available (NSA): false

NR State (NSA): NONE

NR Frequency: UNKNOWN

Network Slicing Config: Unable to get slicing config.

eUICC info: { Available memory in bytes:1289060 }

## Set Preferred Network Type:

GSM/WCDMA/LTE (PRL)



Mobile Radio Power



Test real satellite non-eSOS mode (Debug Build only)

Satellite Config Viewer

VoLTE Provisioned

